

# **PRODUCT DATASHEET**

# Recesse Mounted Panel Light HYD-227R-9W 6500K



## Application

- Household living room
- Mall
- Commercial place
- Corridors
- Hotel

### Benefit

- Internal reflector to increase optical efficiency
- Flicker free
- Low lumen depreciation
- Detachable driver design or DOB design could be option

#### Feature

- Warranty 5 years
- Yellowing-resistant diffuser (PC)
- Buckle design, easy and quick installation
- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain




#### **Electrical Data**


Nominal wattage (W)	9W		
Nominal Voltage (V)	220-240V		
Mains Frequency (Hz)	50-60Hz		
Nominal Current (mA)	80		
LED Driver Current (mA)	300		
LED Driver Voltage (V)	30-42		
LED Driver Efficiency (%)	83%		
Power factor $\lambda$	0.5C		
Total harmonic distortion (%)			
Operating mode	External LED driver		

### **Photometrical data**

Luminous flux ±10% (Im)	943 lm
Luminous efficacy	103 lm/W
Color temperature	6500K
Light color (designation)	Cold White
Color rendering index Ra	≥80
Standard deviation of color matching	≤5 SDCM
Luminous intensity	417 cd
Flickering	Flicker free
Beam angle	98 °



AVERAGE BEAM ANGLE (50%) :97.6 DEG




November,20, 2023 Product Datasheet HYD-227R-9W 6500K **IES** 



# **Dimensions & Weight**

Diameter (mm)	120
Height (mm)	50
Product weight (g)	



D120 mm

### Material & Colors

Product color	Black housing / White Light Cup		
Housing color	White		
Body material	Aluminum		
LGP material	PC		
Mercury content	0.0 mg		

# **Application & Mounting**

Ambient temperature range	-20°C~+45 °C		
Temperature range at storage	-25°C~+60 °C		
Type of connection	Screwless terminal		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recesse mounted		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	110		
LED module replaceable	Not replaceable		
With light source	Yes		




#### **Certificates & Lifespan**

Life (h)	50,000		
Certificates	CB / CE / LVD / RoHS		
Standards	ISO9001:2015		

### **Logistical Data**

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-227R-9W	67*32*37.5 cm	50		0.08040 m <sup>3</sup>

### **Installation Method**



### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

November,20, 2023 Product Datasheet HYD-227R-9W 6500K